

## PRODUCT DATA SHEET

### Mono-grade SAE 10W API CF/SF

#### Description:

**Mono-grade SAE 10W API CF/SF** is an economical approach to many aspects of lubrication and hydraulic application. The product may be used as a transmission and a hydraulic fluid in certain items of static and mobile plant and equipment, both on and off highway, where the viscosity is appropriate.

#### Benefits:

- Monograde
- High viscosity index
- High stability in operation
- Exceptional detergency level
- Very high dispersancy level
- Excellent antiwear and anticorrosion properties
- Excellent antioxidant, antirust and antifoaming properties

#### Application:

**Mono-grade SAE 10W API CF/SF** is recommended for hydraulic systems when the manufacturer requires engine oil with an appropriate grade for these applications.

#### Typical Characteristic:

PARAMETERS	UNIT	Specification	TEST METHODS
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	5.5 – 6.7	ASTM D7042
Viscosity Index	-	Min. 100	ASTM D2270
Total Base Number	mg KOH/g	Min. 11	ASTM D2896
Flash Point	°C	Min. 190	ASTM D93
CCS @ -25°C	cP	Ma. 7000	ASTM D5293

**Product Performance Claim:**

API CF/SF

**Safety Information:**

**Mono-grade SAE 10W API CF/SF** is unlikely to present any significant health or safety hazard when properly used in recommended application and if good standards of industrial and personal hygiene are maintained.

- **Eye:** If irritation or redness develops, flush eyes with clean water. If symptoms persist, seek medical attention.
- **Skin:** Wipe material from skin and wash with mild soap and clean water. If irritation or redness develops, seek medical attention.

**Storage:**

All packages should be stored under cover. Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should be kept in a cool, dry, well ventilated place not above 60 degree Celsius.

**Protect the Environment:**

Dispose used oil to an authorized collection point in compliance to the local authority regulation. Do not discharge used oil into drains, soil or water.