



PRODUCT DATA SHEET

Mineral Diesel Engine Oil

SAE 15W-40 API CI-4/SL

Description:

Mineral Diesel Engine Oil SAE 15W-40 API CI-4/SL is high quality proven premium engine oil formulated for the use in most severe on-highway and off-highway applications. It is specially engineered for modern, high output, low-emission engines including those fitted with Exhaust Gas Recirculation (EGR) as well as older high speed, turbocharged engines running on low sulfur diesel or conventional high sulfur diesel.

Benefits:

- Excellent control over soot induced wear
- High temperature piston deposits, corrosion, foaming and oxidation stability
- Keeps engine clean and minimize deposits to prolong engine life.

Application:

Engine Oil SAE 15W-40 API CI-4/SL is suitable for use in Naturally aspirated and turbo-charged diesel-powered equipment, on-highway light and heavy-duty trucking, off-highway industries including construction, mining, quarrying, and agriculture, and mixed fleet applications where the manufacturer recommends an API CI-4 or earlier specification.

Typical Characteristic:

PARAMETERS	UNIT	Specification	TEST METHODS
Kinematic Viscosity @ 100°C	mm ² /s	13.5 – 15.5	ASTM D7042
Viscosity Index	-	Min. 125	ASTM D2270
Total Base Number	mg KOH/g	Min. 8	ASTM 2896
Flash Point	°C	Min. 190	ASTM D93
Pour Point	°C	Max. -25	ASTM D97
CCS @ -20°C	cP	Max. 7000	ASTM D5293

Product Performance Claim:

API CI-4/SL

Safety Information:

In line with safe handling practices, it is recommended that the handling instructions outlined in the Safety Data Sheet be followed. Store in a cool, dry, well ventilated area out of direct sunlight. Avoid sparks, flames and other ignition sources. Store away from incompatible materials such as materials that support combustion (oxidizing materials).

New or used material must not be allowed to enter the ground, ground water, water courses, sewers or drainage systems. Advice may be sought from the Environmental Protection Authority or from the local waste disposal authority.