

PRODUCT DATA SHEET

Petrol Engine Oil SAE 5W-40 API SN/CF

Description:

Petrol Engine Oil SAE 5W-40 API SN/CF is ultra high performance synthetic multi grade engine oil which meets API SN specification. This oil is developed with high-quality synthetic base oils and latest additive technology and is recommended as an all-season oil in high performance gasoline and direct-injection diesel engines including turbocharged and highly forced sport cars engines.

Benefits:

- Excellent low temperature pumpability and engine cold start.
- Reliable protection against wear and corrosion in severe conditions of urban cycle.
- Special attention paid to the detergent/dispersant properties.
- Adapted to operate at higher revolutions
- Prevention of high and low temperature deposits on the engine components
- Safe to catalyst converters

Application:

Petrol Engine Oil SAE 5W-40 API SN/CF is suitable for all types of modern vehicles, including high-performance turbo-charged, supercharged gasoline and certain diesel multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks where the manufacturer recommends an API SN or earlier specification.

Typical Characteristic:

PARAMETERS	UNIT	Specification of 5W-40		TEST METHODS
		<i>Semi-Synthetic</i>	<i>Fully Synthetic</i>	
Kinematic Viscosity @ 100°C	mm ² /s	13.5 – 15.5		ASTM D7042
Viscosity Index	-	Min. 135	Min. 160	ASTM D2270
Total Base Number,	mg KOH/g	Min. 6		ASTM 2896
Flash Point	°C	Min. 190		ASTM D93
Pour Point	°C	Max. -35		ASTM D97
CCS @-30°C	cP	Max. 6600		ASTM D5293

Product Performance Claim:

API SN/CF

Safety Information:

Petrol Engine Oil SAE 5W-40 API SN/CF is unlikely to present any significant health or safety hazard when properly used in recommended application and if good standards of industrial and personal hygiene are maintained.

- **Eye:** If irritation or redness develops, flush eyes with clean water. If symptoms persist, seek medical attention.
- **Skin:** Wipe material from skin and wash with mild soap and clean water. If irritation or redness develops, seek medical attention.

Storage:

All packages should be stored under cover. Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should be kept in a cool, dry, well ventilated place not above 60 degree Celsius.

Protect the Environment:

Dispose used oil to an authorized collection point in compliance to the local authority regulation. Do not discharge used oil into drains, soil or water.