



PRODUCT DATA SHEET

Mineral Engine Oil
SAE 15W-40 API SN/CF

Description:

Mineral Engine Oil SAE 15W-40 API SN/CF is a high performance engine lubricant, designed to meet the requirements of a wide range of naturally aspirated and turbo charged petrol and light duty Diesel engines.

Benefits:

- Very high resistance against oxidation
- High detergent and dispersing properties
- Very large application field
- Low loss by evaporation
- High performance in high and low temperature conditions
- Excellent protection against wear

Application:

Engine Oil SAE 15W-40 API SN/CF is an all season's oil, especially recommended for mixed fleets (passenger cars and light commercial vehicles). It can be used in most services, in Diesel engines with natural aspiration or with turbo discharge and in most petrol engines.

Typical Characteristic:

PARAMETERS	UNIT	Specification	TEST METHODS
Kinematic Viscosity @ 100°C	mm ² /s	13.5 – 15.5	ASTM D7042
Viscosity Index	-	Min. 120	ASTM D2270
Total Base Number	mg KOH/g	Min. 6	ASTM 2896
Flash Point	°C	Min. 190	ASTM D93
Pour Point	°C	Max. -25	ASTM D97
CCS @ -20°C	cP	Max. 7000	ASTM D5293

Product Performance Claim:

API SN/SM/CF

Safety Information:

Engine Oil SAE 15W-40 API SN/CF is unlikely to present any significant health or safety hazard when properly used in recommended application and if good standards of industrial and personal hygiene are maintained.

- **Eye:** If irritation or redness develops, flush eyes with clean water. If symptoms persist, seek medical attention.
- **Skin:** Wipe material from skin and wash with mild soap and clean water. If irritation or redness develops, seek medical attention.

Storage:

All packages should be stored under cover. Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should be kept in a cool, dry, well ventilated place not above 60 degree Celsius.

Protect the Environment:

Dispose used oil to an authorized collection point in compliance to the local authority regulation. Do not discharge used oil into drains, soil or water.